


SECTION	Width (w) in (mm)	Height (h) in (mm)	Thickness (t) in (mm)	Cross Sectional Area in ² /ft (cm ² /m)	WEIGHT		SECTION MODULUS		Moment of Inertia in ⁴ /ft (cm ⁴ /m)	COATING AREA	
					Pile	Wall	Elastic	Plastic		Both Sides	Coating Area
					lb/ft (kg/m)	lb/ft ² (kg/m ²)	in ³ /ft (cm ³ /m)	in ³ /ft (cm ³ /m)		ft ² /ft (m ² /m)	ft ² /ft ² (m ² /m ²)
SKL 9	21.65 550	3.54 90	0.157 4.0	2.53 53.50	15.52 23.10	8.60 42.00	2.55 137	3.28 176.43	4.50 615	4.23 1.29	1.17 1.17
SKL 10	21.65 550	3.54 90	0.177 4.5	2.83 59.90	17.40 25.90	9.63 47.00	2.88 155	3.67 197.23	5.09 695	4.23 1.29	1.17 1.17
SKL 12	21.65 550	3.54 90	0.217 5.5	3.43 72.60	21.10 31.40	11.67 57.00	3.53 190	4.42 237.66	6.22 850	4.23 1.29	1.17 1.17
SKS 11	27.56 700	5.91 150	0.197 5.0	3.29 69.60	25.69 38.23	11.26 55.00	6.34 341	7.54 405.36	18.67 2550	5.87 1.79	1.28 1.28
SKS 13	27.56 700	5.91 150	0.217 5.5	3.61 76.40	28.22 42.00	12.29 60.00	6.98 375	8.44 454.03	20.48 2810	5.87 1.79	1.28 1.28
SKS 14	27.56 700	5.91 150	0.250 6.4	4.17 88.20	32.58 48.49	14.19 69.27	8.05 433	9.48 509.87	23.78 3247	5.87 1.79	1.28 1.28
SKS 16	27.56 700	5.91 150	0.276 7.0	4.57 96.70	35.61 53.00	15.57 76.00	8.89 478	10.40 559.20	26.25 3585	5.87 1.79	1.28 1.28

SKL/SKS

SKL/SKS Cold Formed Steel Sheet Piling


Corner Piles



D1 Corner Pile

SKL 9-12
A = 10.8 inches (275.0 mm)

SKS 11-16
A = 13.8 inches (350.0 mm)



D3 Corner Pile

SKL 9-12
A = 10.8 inches (275.0 mm)

SKS 11-16
A = 13.8 inches (350.0 mm)

Delivery Conditions & Tolerances

ASTM

Mass	± 2.5%	
Length	+ 5 inches	- 0 inches
Interlock Opening	± 0.08 inches	
Straightness	0.2% of the length	
Twisting	0.4% of the width	

Standard Rolled Lengths*

SKL, SKS	70 feet	(21.3 m)
----------	---------	----------

* Longer lengths may be possible upon request.

Optional Accessories



Sheet Pile Protector



Waler



Cap



Sheet Pile Protector